	Type	thread	tightening specification	Measure
1AZ Nut to retaining thread, rear light		M5		7 Nm
2AZ Bar to platform		M8x35		23 Nm
3AZ Lashing plate to platform		M8x35		15 Nm
4AZ Front guard to cross-member		M8x55		28 Nm
5AZ Front guard to longitudinal member		M8x25		34 Nm
6AZ Saucer head screw to rail		M5x15		7 Nm
7AZ Rail, loading ramp frame to cross strut		M6x16		11.5 Nm
8AZ Rail, loading ramp frame to longitudinal member mount		M6x16		11.5 Nm
9AZ Cross strut to rail		M6x16		5.5 Nm
10AZ Footplate to drawbar member		M6x25		11.5 Nm
11AZ Bracket to drawbar member		M8x25		34 Nm
12AZ Wiring harness mount to reversing housing		M10x1x20		58 Nm
13AZ Socket holder to drawbar		M10x95		55 Nm
14AZ Top reversing housing and bracket to drawbar member		M10		55 Nm
15AZ Towing attachment to tow tube		M12x70		96 Nm
16AZ Drawbar member to cross-member		M8x20		28 Nm
17AZ Cross-member to drawbar member		M8x25		40 Nm
18AZ Drawbar member to cross-member		M8x25		28 Nm
19AZ Disk wheel to brake hub				100 Nm
20AZ Brake hub to axle				280 Nm
21AZ Shock absorber to bracket		M12x55		96 Nm
22AZ Trailing arm to coil spring		M10x35		46 Nm
23AZ Coil spring to longitudinal member		M10x25		46 Nm
24AZ Wheel brake to trailing arm		M10x1.5x30		145 Nm

25AZ Trailing arm to mount		M12x85		96 Nm
26AZ Rear apron to bracket		M8x25		26 Nm
27AZ Bracket to mounting bracket		M6x16		11 Nm
28AZ Rotary striker lock to cross strut		M8x35		18 Nm
29AZ Bearing pedestal to loading ramp frame		M6x16		10 Nm
30AZ Outer towbar mount to longitudinal member		M10x25		55 Nm
31AZ Mounting bracket to longitudinal member		M10x25		78 Nm
32AZ Base plate to cross-member		M10x35		78 Nm

	Type	thread	tightening specification	Measure
1AZ Roof railing, front and rear, to roof railing adapter		M8		22.5 Nm
2AZ Roof railing, middle, to roof railing adapter		M8		22.5 Nm
3AZ Roof railing, front and rear, to support		M6		15 Nm
4AZ Roof railing, middle, to support		M6		10 Nm
5AZ Upper lock striker fixture to lower lock striker fixture		M8		27 Nm
6AZ Hinge, side lid, to support		M8		27 Nm
7AZ Support, lid to lid		M8		23 Nm
8AZ Screw, depth adjustment, side lid		M8		27 Nm
9AZ Screw, depth adjustment, rear lid		M8		27 Nm
10AZ Ball pivot to retaining bracket		M8		23 Nm
11AZ Retaining bracket to support		M8		27 Nm
12AZ Rotary striker lock to support		M5		7 Nm